Camden PassivHaus, London, by Bere Architects

The project is a 120m² single family house split over two floors, with two wild flower meadow roofs and a south-facing garden. The house superstructure was prefabricated in Austria. Walls are 240-280mm thick prefabricated insulated timber framed panels clad in the factory with European larch fixed to untreated softwood battens.

CO₂ emissions have been minimised with insulation, draught-free construction, triple-glazed windows and a solar thermal panel. All details were thermally modelled by the architects to prevent cold bridges and eliminate cold spots that would risk mould growth and damp patches. Automatic solar shading by external venetian blinds on the south elevation will control heat gains in summer.


The house uses non-toxic materials throughout, together with heat-recovery ventilation and water filtration. Careful attention has been given to unregulated energy consumption; while any heat required will come from the air supply, a towel radiator has been installed in each ensuite bathroom. Towel rails are controlled by a switch with a 30, 60 or 120 minute option before switching off. An internal ventilated clothesdrying room and external concealed south-facing clothes drying space discourage tumble drying.

Credits

Start on site September 2009
Completion Summer 2010
PassivHaus certification April 2010
Annual heat demand 13 kWh/(m²a)
Primary energy demand 90 kWh/(m²a)
Annual CO₂ emissions 10.2kg/m²
Air test result 0.4m³ (m²h)
Insulation Ground floor slab: 380mm wood fibre. Walls: 280mm mineral wool +100mm wood fibre. Flat roof: 280mm PUR + 120mm mineral wool. Sloping roof: 380mm mineral wool. Terrace: 130mm PUR



Above Structured panels with cladding were prefabricated



- 1. Bedroom
- 2. Bedroom
- 3. Bathroom 4. WC
- 5. Utility/plant
- 6. HRV
- 7. Cycle storage 8. HRV
- 9. lvy-covered gabion wall



60